

# JET 2000 RS

- SYNTHETIC PLUS -

Standards : API TD – TC-W3

**Jet 2000 RS** is a high-quality synthetic lubricant developed for two-stroke jet-skis, designed for leisure use. IPONE has selected the best quality synthetic bases and the most suitable additives to comply with the marine TC-W3 standard and guarantee optimal protection for your engine.



● **Packaging:** \_\_\_\_\_

● **Technical data:**

TEST	METHOD	TYPICAL VALUES	UNITS OF MESURE
DENSITY AT 20° C	ISO12185	0,863	G/cm <sup>3</sup>
VISCOSITY AT 100° C	ASTM D445	9,1	mm <sup>2</sup> /s
VISCOSITY AT 40° C	ASTM D445	57	mm <sup>2</sup> /s
VISCOSITY INDEX (VIE)	ASTM D 2270	138	-
FLASH POINT	ASTM D92	138	°C
POUR POINT	ASTM D97	-45	°C
TBN	ASTM D2896	5,3	mgKOH/g
TAN	ASTM D664	1,12	mgKOH/g



La Meunière - CS 10001 - FR 13480 CABRIÈS - TÉL. : +33 4 42 94 05 65 - Fax : +33 4 42 94 05 66

info@ipone.fr - www.ipone.com -  /iponelube -  /iponelube -  iponelube